



Maximize Productivity with the High Performance HCT-910 Hot Air Rework System

The Metcal HCT-910 Hot Air Rework System offers a versatile solution for a wide variety of production and rework applications.

Features

- Versatile 900 W fast-heating hot air tool for soldering and desoldering applications
- Max temperature of 600 °C (1112 °F)
- Max airflow up to 120 l/m (4.2 cfm)
- Digital controls for both airflow & temperature, for increased precision
- On-the-fly manual mode quickly toggle between temperature and flowrate
- Handpiece start/stop button & status light
- Tool-less nozzle removal & replacement
- ESD compliant
- TUV certified, CE listed

metcal.com/contact-us



TECHNICAL SPECIFICATIONS

| | HCT-910-11 | HCT-910-21 |
|-------------------------------|--|---------------|
| Input Voltage (V) | 115 V / 60 Hz | 230 V / 50 Hz |
| Power | 900 W | |
| Temperature Range | 50 - 600 °C (122 - 1112 °F) | |
| Temperature Accuracy | ± 30 °C (54 °F) | |
| Air Flow | At 300 °C, 5 - 120 I/m (0.2 - 4.2 cfm) | |
| Air Pump Type | Blower | |
| Hose Length (Panel-Handpiece) | 1.2 m (3.9 ft) | |
| Noise | < 46 dB (A) | |
| Weight | 2 kg (4.4 lbs) | |
| Safety Class | 1 | |
| Pollution Degree Category | II | |
| Storage Temperature | 0 - 60 °C (32 - 140 °F) | |
| Surface Resistivity | Unit: 10^{5}_{Ω} - 10^{6}_{Ω} . Handpiece & Tube: 10^{7}_{Ω} - 10^{11}_{Ω} | |
| Dimensions | 21 x 14 x 14 cm (8.3 x 5.5 x 5.5 in) | |
| Certification/Approvals | cTUVus, CE, RoHS | |

SYSTEMS SHIP WITH

HCT-910 Base Unit 5.0 mm Ø Bayonet Nozzle Hand-piece Cradle Power Cord

ACCESSORIES (sold separately)

| HCT-910-HE-11 | HCT-910 Replacement Heater, 115 V Input |
|---------------|---|
| HCT-910-HE-21 | HCT-910 Replacement Heater, 230 V Input |
| HB-D25 | HCT-910 Nozzle, Bayonet, 2.5 mm Ø |
| HB-D50 | HCT-910 Nozzle, Bayonet, 5.0 mm Ø |
| HB-D100 | HCT-910 Nozzle, Bayonet, 10.0 mm Ø |
| HB-D25-B | HCT-910 Bent Nozzle, Bayonet, 2.5 mm Ø |
| HB-D50-B | HCT-910 Bent Nozzle, Bayonet, 5.0 mm Ø |
| HB-ST | HCT-910 Nozzle, Bayonet, Shrink Tube |

HCT-910 Nozzles are compatible with legacy HCT-900 and HCT- 1000 series systems. Visit Metcal.com for the full offering of nozzles.

Authorized Distributor Mectronics Marketing Services 313, 2nd Floor, Patparganj Industrial Area, New Delhi - 110092 (India) Tel : +91 (011)-43041581 / 42208256 E-Mail : mectronics@mectronics.in Web : www.mectronics.in

For Sales and Support:

Metcal Corporate Headquarters 10800 Valley View Street, Cypress, California, 90630, USA Tel: 1-714-799-9910 Fax: 1-714-828-2001 E-mail: eorders@okinternational.com Visit our website for more information and to contact the Metcal office nearest you. We have several offices worldwide that are ready to serve your needs.

🕑 in 🗗

metcal.com/contact-us